THE SPECIALTY MFG. CO.

5858 Centerville Road St. Paul, MN 55127 www.specialtymfg.com

027 Series Ball Valve



Configure your exact valve



Design Considerations

- The 027 Two-Way Ball Valves are rated to 500 psi and will support flow and pressure in either direction
- A one-piece body construction and Zinc Die Cast Lever Handle is standard
- Handles can be ordered reversed to lie over the outlet when the valve is in the open position
- UL configurations Contact us 651.653.0599
- UR configurations Contact us 651.653.0599

Specifications:

	Maximum Operating Pressure- 500 psi	Maximum Operating Temperature- 180°F			
Material	BODY and ENDS - Brass, BALL - Nickel Plated Brass, SEATS - Teflon®, HANDLE SCREW - Stainless				
Туре	TWO-WAY - Supports Flow and Pressure in either direction				
Body Option	1/4 Female NPT Inlet x 1/8 Male NPT Outlet (4 F2M) 1/4 Female NPT Inlet x 1/4 Female NPT Outlet (4 F4F) 1/4 Female NPT Inlet x 1/4 Male NPT Outlet (4F4M)				
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®), Neoprene, AFLAS®, Perfluoroelastomer				
Plating Option	No Plating, Electroless Nickel Plating				
Handle Option	Zinc Die Cast Lever Handle Zinc Die Cast Lever Handle (No Stops) Zinc Die Cast Lever Handle, Reversed Zinc Die Cast Lever Handle with Red Vinyl Sleeve Zinc Die Cast Lever Handle with Red Vinyl Sleeve, Reversed Steel Lever Handle Steel Lever Handle, Reversed	Steel Lever Handle with Red Vinyl Sleeve Steel Lever Handle with Red Vinyl Sleeve, Reversed Round Zinc Die Cast Handle Black Nylon T-Handle Blue Nylon Plastic Handle Screw Slot Headed Ball Zinc Die Cast Stem312 X 1"			
Cv	1.66 with 1/4 Female (4F) NPT Ends				
Ball Flow Pattern Option	0.218 Through Hole 0.062 Through Hole 0.040 Cross Hole 0.087 Cross Hole				

Example of how to order:

Туре	Inlet End	Outlet End	Seal	Handle	Plating
Brass, Two-Way	1/4 Female NPT	1/4 Female NPT	Buna	Steel	No Plating

Part Number 027-4F4F-BT,SH

Part Numbers are a description of the valve as read left to right, Inlet to Outlet. Example: 027-4F4F-BT,SH = Brass Two-Way Ball Valve, 1/4 Female NPT Inlet x 1/4 Female NPT Outlet, Buna Seals, Steel Handle, Unplated