

## 515 SERIES THUM-GUN

1/4" NPT



Configure your exact valve



SCAN ME

### Design Considerations

- The 515 Thum-Gun is designed for comfort and ease of operation
- The natural position of the vinyl covered handle and easy action thumb operated trigger minimize user fatigue
- Features a shielded trigger with safety lock to prevent accidental trigger operation
- Rated to 1500 psi, the stainless ball on a stainless seat requires approximately 200 psi minimum operating pressure to seal
- Applications under 500 psi where a positive shut off is required - a Soft Viton® Seat option is available
- Seal, Soft Seat and Hard Seat Repair Kits are available, economical and easy to install

### Specifications:

<b>Material</b>	BODY - Electroless Nickel Plated Brass, TRIGGER GUARD and STOP - Nickel Plated Steel, SPRING - 302 Stainless, PIN and BALL - 440 Stainless
<b>Body Option</b>	1/4 Female NPT Inlet x 1/8 Female NPT Outlet
<b>Seal Option</b>	Buna-N Fluoroelastomer (Viton®)
<b>Seat Option</b>	303 Stainless Viton® Soft Seat
<b>Handle Option</b>	Black Vinyl Grip Handle No Handle
<b>Maximum Operating Pressure</b>	1500 psi
<b>Maximum Operating Temperature</b>	180 °F
<b>Repair Kit / Replacement Parts Options</b>	515 Buna Seal Kit (5260390) 515 Viton Seal Kit (5260990) 515 Viton Seat, Seal & Pin Kit (5261490)

### Example of how to order:

Material	Seals	Seat	Handle
Nickel Plated Brass Body	Viton®	303 Stainless	Vinyl Grip Handle

**Part Number:** 515 THUM GUN-F

Part Numbers are a description of the thum gun.

Example: 515 THUM GUN-F = Nickel Plated Brass Thum Gun , 1/4 Female NPT Inlet x 1/8 Female NPT Outlet, Viton® Seals, 303 Stainless Seat, Black Vinyl Grip Handle