

693 Series Poppet Check Valve

3/8" NPT



Configure your exact valve



SCAN ME

Design Considerations

- The 693 Poppet Check Valve incorporates a thin elastomer disc supported by a poppet that seals on the seat
- Pressure in the flow direction moves the seal off the seat at about 1/3 psi before pressure builds enough to move the poppet away from the seat
- Maximum operating pressure of 125 psi covers a wide range of air and fluid applications
- Compact design with a light cracking pressure, high flow rate, and a positive seal at very low back pressure or slight vacuum
- An embedded O-Ring Poppet is supplied for cracking pressure applications 1/2 psi and higher
- Hastelloy® is a superior chemically resistant spring material

Specifications:

Material	Black Glass Filled Polypropylene, White Glass Filled Polypropylene Black PVDF (Kynar®)	
Inlet End	3/8 Female and Male NPT	
Outlet End	3/8 Female and Male NPT	
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®), Viton® Extreme, Silicone, AFLAS® *** Please ask us about Seal Materials not listed above. ***	
Spring Option: Cracking Pressure and Material	1/3 psi - 302 Stainless (Disc Poppet) .5 psi - 302 Stainless (O-Ring Poppet) 1 psi - 302 Stainless (O-Ring Poppet) 7 psi - 302 Stainless (O-Ring Poppet) 9 psi - 302 Stainless (O-Ring Poppet)	14 psi - 302 Stainless (O-Ring Poppet) 1/3 psi - Hastelloy® (Disc Poppet) 1 psi - Hastelloy® (O-Ring Poppet) 2 psi - Hastelloy® (O-Ring Poppet)
Maximum Flow Diameter	0.562 in	
Cv	4.2 with 3/8 Female NPT Ends	
Maximum Operating Pressure	125 psi	
Maximum Operating Temperature	140 °F	

Example of how to order:

Material	Inlet Port	Outlet Port	Seal	Spring
White Glass Filled Polypropylene	3/8 Female NPT	3/8 Female NPT	Buna	1/3 psi

Part Number WFP CHK 693-6F6F-B,DP,1/3#

Part Numbers are a description of the check valve as read left to right, Inlet Port to Outlet Port.

WFP CHK 693-6F6F-B,DP,1/3# = White Glass Filled Polypropylene Check Valve, 3/8 Female NPT Inlet x 3/8 Female NPT Outlet, Disc Poppet, Buna Seals, 1/3 psi Spring