

## 900 Series Swivel

3/8" NPT



Configure  
your exact valve



SCAN ME

### Design Considerations

- The 900 Swivel promotes a compact design for 3/8 NPT fluid hose and air line applications
- Maximum Operating Pressure - 1000 psi
- Bronze Thrust Bearing for low torque with a Buna-N seal is standard
- Ethylene Propylene and Viton® seals are available

### Specifications:

<b>Material</b>	BODY and ENDS - Brass, THRUST BEARING - Bronze
<b>Body Option</b>	3/8 Female NPT x 3/8 Male NPT 3/8 Male NPT x 3/8 Barb
<b>Seal Option</b>	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)
<b>Through Hole Diameter</b>	0.312
<b>Maximum Operating Pressure</b>	1000 psi
<b>Maximum Operating Temperature</b>	180 °F

### Example of how to order:

Type	Inlet	Outlet	Seal
Inline Swivel	3/8 Female NPT	3/8 Male NPT	Viton®

**Part Numbers** are a description of the swivel as read left to right, Inlet Port to Outlet Port.

**SWIVEL 900-6F6M-F=** Brass Inline Swivel, 3/8 Female NPT x 3/8 Male NPT, Viton® Seals