

928 Series Swivel

1/4" to 3/8" NPT



Configure your exact valve



SCAN ME

Design Considerations

- The 928 Swivel promotes a compact design for 1/4 NPT and 3/8 NPT fluid hose and air line applications
- Maximum Operating Pressure - 1500 psi
- Polyphenylene Sulfide Thrust Bearing for low torque with a Buna-N U-Cup seal is standard
- Viton® seals are available
- Seal Repair Kits are available

Specifications:

Material	BODY and ENDS - Nickel Plated Brass, THRUST BEARING - Glass Filled Polyphenylene Sulfide
Inlet End	1/4 Female NPT 3/8 Female NPT
Outlet End	1/4 Male NPT, 1/4 Female NPT 3/8 Male NPT, 3/8 Female NPT
Seal Option	Buna-N, Fluoroelastomer (Viton®)
Through Hole Diameter	0.312
Maximum Operating Pressure	1500 psi
Maximum Operating Temperature	180 °F
Repair Kit / Replacement Parts Options	928 Repair Kit - Buna (5230690) 928 Repair Kit - Viton (5231190)

Example of how to order:

Type	Inlet	Outlet	Seal
Inline Swivel	1/4 Female NPT	1/4 Male NPT	Viton®

Part Numbers are a description of the swivel as read left to right, Inlet Port to Outlet Port.

SWIVEL 928-4F4M-F= Brass Inline Swivel, 1/4 Female NPT x 1/4 Male NPT, Viton® Seals