

## THE SPECIALTY MFG. CO.

5858 Centerville Road St. Paul, MN 55127 **SMC** will quote alternate materials or customize our standard products when quantities ensure competitive pricing. **Contact Customer Service** at (651) 653-0599

**FAX** - (651) 653-0989

E-Mail - info@specialtymfg.com

### M-170 FILTER 1/8" to 1/4" NPT



### **Design Considerations**

Inline Filter

- The M-170 Filter has a two piece body and end construction for easy cleaning
- 35 Micron Bronze replaceable filter element

1/4 Female NPT

- Available in 1/8 and 1/4 Female NPT
- Rated to 500 psi and will support flow and pressure in either direction

# <u>Type Inlet Outlet Seal Filter</u>

Part Numbers are a description of the filter as read left to right, Inlet End to Outlet End.

M-170-4F4F-B,35M = Nickel Plated Brass Filter, 1/4 Female NPT x 1/4 Female NPT, Buna-N Seals, 35 Micron Bronze Filter Element

1/4 Female NPT

Buna-N

35 Micron

#### **Specifications**

| Material                                 | Electroless Nickel Plated Brass  |
|--|--|
| Filter Element                           | 35 Micron Bronze Filter Element  |
| Body Option                              | 1/8 Female NPT Inlet x 1/8 Female NPT Outlet<br>1/4 Female NPT Inlet x 1/4 Female NPT Outlet   |
| Seal Option                              | Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)   |
| Maximum Operating Pressure               | 500 psi  |
| Maximum Operating Temperature            | *** NOT RATED FOR STEAM ***  Buna-N -10°F to +250°F  Ethylene Propylene (EPDM) -50°F to +300°F  Fluoroelastomer (Viton®) -10°F to +375°F   |
| Compatibility Statement                  | It is the sole responsibility of the system designer and user to select products suitable for their specific application requirements and to ensure proper installation, operation, and maintenance of these products.  Material compatibility, product ratings and application details should be considered in the selection. Improper selection or use of products described herein can cause personal injury or product damage. |
| Pricing and Minimum Order<br>Requirement | Our Minimum Order Requirements are \$100.00 Domestic - \$250.00 International. Pricing is based on the quantity ordered. Please indicate a typical order quantity or Estimated Annual Usage when requesting pricing.   |