

Male Quick Disconnect (without valve)



Design Consideration



- Male Quick Disconnect
- Without Valve

Example of how to order

Type: Male Quick Disconnect **Body:** Without Valve **End Option:** 10-32 Female

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port.

QD MALE,W/O VALVE,10-32F = Male Quick Disconnect, Without Valve, 10-32 Female

Item #	Image	Body	End Option	Maximum Operating Pressure	Maximum Operating Temperature
QD MALE,W/O VALVE,10-32F	 QD MALE,W/O VALVE,10-32F larger image	QD MALE,W/O VALVE	10-32 Female	125 psi	180 °F
QD MALE,W/O VALVE,10-32M	 QD MALE,W/O VALVE,10-32M larger image	QD MALE,W/O VALVE	10-32 Male	125 psi	180 °F

Item #	Image	Body	End Option	Maximum Operating Pressure	Maximum Operating Temperature
QD MALE, W/O VALVE, 1/16B	 <p>QD MALE, W/O VALVE, 1/16B larger image</p>	QD MALE, W/O VALVE	1/16 Barb	125 psi	180 °F
QD MALE, W/O VALVE, 3/32B	 <p>QD MALE, W/O VALVE, 3/32B larger image</p>	QD MALE, W/O VALVE	3/32 Barb	125 psi	180 °F
QD MALE, W/O VALVE, 1/8B	 <p>QD MALE, W/O VALVE, 1/8B larger image</p>	QD MALE, W/O VALVE	1/8 Barb	125 psi	180 °F