

Swivel Needle Valve (Female x Female)

Configure your exact valve



1/8" NPT

Design Considerations

- 1/8 NPT Swivel Body for easy orienation after installation
- 6.5 Turn Adjustment Needle
- Smooth or Ribbed ABS Knob in Black or Gray

* * * Knobs are Optional * * *

Specifications:

Туре	Needle Valve			
Material	BODY - Electroless Nickel Plated Brass			
Needle Option	6.5 Turn Brass			
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)			
Input Port	1/8 Female NPT			
Output Port	1/8 Female NPT			
Knob	No Knob Smooth Black ABS, Smooth Gray ABS Ribbed Black ABS, Ribbed Gray ABS			
Maximum Operating Pressure	0 to 125 psi			
Maximum Operating Temperature	180 °F			
Flow Rate	2.5 SCFM at 50 psi			

Example of how to order:

Туре	Seal	Needle	Inlet Port	Outlet Port	Knob
Swivel Needle Valve	Buna	6.5 Turn Needle	1/8 FNPT	1/8 FNPT	No Knob

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port.

Example: SWNV2NC-B,6.5T,1/8F,NO KNOB= Swivel Needle Valve, Buna Seals, 6.5 Turn Needle, 1/8 Female Inlet x 1/8 Female Outlet, No Knob